



D249 Steam

Innovative. Efficient. Dependable. Dunkirk

D249 Steam

Commercial Gas Fired Steam Boiler

Electronic Ignition Base Standard Equipment:

- Base
- Fire Door
- Burner Orifice
- Manifold
- Main and Pilot Burner
- Electronic Pilot Gas Valve
- Intermittent Pilot Module
- Complete Jacket Assembly

Steam Trim Package:

- Low Water Cut-Off
- Glass Gauge Set
- Safety Valve
- Steam Gauge
- Pressure Limit
- Drain Valve

D249 Series Boiler Bases are pre-assembled at the factory with burner manifold, burner orifices, gas valves and electronic ignition installed, ready for field installation of the pre-tested sections and appropriate packages.

Plug 'N Play Harness and Junction Box

Individual base and junction box controls are designed for easy installation with Plug 'n Play harnesses. The entire boiler links together in a "snap". A color-coded factory supplied harness eliminates wiring errors.

CSD1 Option

D249 boilers are available with a CSD1 option to comply with CSD1 standards where required by building code. The CSD1 option provides the increased number of controls and safety devices required to meet CSD1 standards.




www.dunkirk.com

PN 240009440 Rev. [09/10/19]

Dunkirk D249 Commercial Gas-Fired Steam Boiler

Model	Input (Mbh) ⁽¹⁾	Gross Output (Mbh)	Net AHRI Ratings			Base Size & Flue Outlet			Chimney Size ⁽⁴⁾ I.D. x Ht.	Vent Connector Size to Chimney ⁽⁴⁾	Thermal Efficiency
			Steam (PPF) ⁽²⁾	Steam (Sq. Ft.) ⁽³⁾	Steam (Mbh) ⁽²⁾	300 (8")	400 (10")	500 (12")			
D249300S	300	233	1.333	729	175	1	0	0	8" x 20'	8	77.0
D249400S	400	310	1.333	971	233	0	1	0	10" x 20'	10	77.0
D249500S	500	388	1.333	1213	291	0	0	1	12" x 20'	12	77.0
D249600S	600	465	1.333	1454	349	2	0	0	12" x 20'	12	77.0
D249700S	700	543	1.333	1696	407	1	1	0	12" x 20'	12	77.0
D249800S	800	620	1.333	1938	465	0	2	0	14" x 20'	14	77.0
D249900S	900	698	1.333	2183	524	0	1	1	14" x 20'	14	77.0
D2491000S	1000	775	1.333	2421	581	0	0	2	14" x 20'	14	77.0
D2491100S	1100	853	1.333	2667	640	1	2	0	16" x 20'	16	77.0
D2491200S	1200	930	1.333	2908	698	0	3	0	16" x 20'	16	77.0
D2491300S	1300	1008	1.333	3150	756	1	0	2	16" x 20'	16	77.0
D2491400S	1400	1085	1.333	3392	814	0	1	2	18" x 20'	18	77.0
D2491500S	1500	1163	1.333	3633	872	0	0	3	18" x 20'	18	77.0

Right & Left End Tappings Data




"If opening F is to be used for something other than the Safety Valve or Pressure Relief Valve, or the Safety/Relief Valve is larger than 1", the Safety/Relief Valve must be installed in the Header Piping as

Opening	Size	Steam
A	4"	Supply and Return
B	1/2"	Primary LWCO and Gauge Glass set
C	3/4"	Drain, Left End
C	3/4"	Drain, Right End
D	1/2"	Plugged
E	1"	Accessories
*F	1"	Safety Valve
G	3/4"	Plugged or Electronic (Probe Type) LWCO

1. Ratings are at sea level to 2,000 feet. For altitudes above 2,000 feet, reduce all ratings 4% for each 1,000 feet above sea level.
2. Net steam ratings based on piping and pickup allowance of 1.333 (300-1500). Contact Technical Support before selecting boiler for installations having unusual piping and pick-up factors, such as intermittent system operations, extensive piping systems, etc.
3. Ratings in square feet are computed at 240 Btuh/square foot for steam boilers.
4. Chimney sizes shown are one option based on a typical venting system as shown in Figure 6 of the Installation Manual, and sized according to the National Fuel Gas Code, assuming Type B double wall vent and vent connectors, other venting system designs are acceptable as shown on Flue Connection And Venting section of the installation manual. For further chimney design and sizing information, consult the National Fuel Gas Code, ANSI Z223.1/NFPA 54-latest revision, or ASHRAE HVAC Systems and Equipment Handbook, Chimney, Gas Vent, and Fireplace Systems, or the Standard for Chimneys, Fireplaces, Vents, and Solid Fuel Burning Appliances. NFPA 211. Follow standard engineering practice.

Certifications



ECR International, Inc. 2201 Dwyer Avenue, Utica, NY 13501
Tel. 800 253 7900
www.ecrinternational.com

All specifications subject to change without notice.
©2019 ECR International, Inc.
PN 240009440 Rev. [09/10/19]