

Dunkirk® | Q95M-200

Innovative. Efficient. Dependable. Dunkirk.











Q95M-200

95% AFUE Residential Gas Fired Modulating Condensing Boiler

- High Efficiency Cast Aluminum Monoblock Heat Exchanger with low pressure drop.
- Microprocessor Based Modulating Control.
 - Monitors the supply and return water temperature, adjusting the boiler firing rate to match the building load conditions.
- Hi-Limit Control with LED display and self diagnostic features.
- Low Water Cut Off.
- Boiler Temperature Reset.
 - Lowers the boiler supply water temperature depending on outdoor air temperature. Saves fuel without sacrificing comfort.
- Domestic Hot Water Priority.
- Easy to Install & Service.
 - Intake and flue gasses can be piped with readily available 3" PVC up to 100 equivalent feet.
 - Option of left, right, or rear exit for return plumbing and gas piping.
 - Piping connections facilitate multiple boiler installations.
 - Integral Condensate Trap.
- Limited 15 Year Warranty.



Dunkirk Q95M-200 Natural or Propane Gas-Fired Modulating Condensing Hot Water Boiler

Dimensions/Weights	Model	Boiler Input Rate (MBH) ⁽¹⁾		Heating Capacity (MBH) ⁽¹⁾⁽²⁾		Net AHRI Rating, Water (MBH) ⁽¹⁾⁽³⁾		AFUE % ⁽²⁾	
		Max.	Min.	Max.	Min.	Max.	Min.		
 <p>front</p>  <p>top</p>  <p>left</p>  <p>right</p>  <p>back</p>	Q95M-200	200	80	182	75	158	65	95.0	
	(1) 1000 Btu/hr (British Thermal Units Per Hour)								
	(2) Heating Capacity and AFUE (Annual Fuel Utilization Efficiency) are based on DOE (Department of Energy) test procedures.								
	(3) Net AHRI Ratings based on piping and pickup allowance of 1.15. Contact Technical Support before selecting boiler for installations having unusual piping and pickup requirements, such as intermittent system operation, extensive piping systems, etc.								
	General Information (See Installation, Operation and Maintenance Manual for complete instructions)								
	Clearances (4) Required distances measured from boiler. (5) Service, proper operation clearance recommendation. Note: May be installed on combustible flooring (No Carpets).			Combustible Materials (Required) ⁽⁴⁾		Service ⁽⁵⁾			
		Top		1" (2.5 cm)		8" (20.3 cm)			
		Left Side		1" (2.5 cm)		24" (61 cm)			
		Right Side		1" (2.5 cm)		-			
		Front		0" (0 cm)		24" (61 cm)			
Back		6" (15.2 cm)		-					
Bottom		1" (2.5 cm)		-					
Combustion Air/Vent Piping		0" (0 cm)		-					
Combustion Air & Vent Pipe Equivalent Length			3" Pipe						
	Min. Length		15 Ft. (4.6 m)						
	Max. Length		100 Ft. (30.5 m)						
	Vent Pipe - First 2.5' (.762 m) is Schedule 80 2" CPVC (provided), then Schedule 40 3" PVC.								
	Air Intake - Schedule 40 3" PVC.								
Notes: 3" Pipe Min. Venting - 15 ft. equivalent length, 3" Pipe Max. Venting - 100 ft. equivalent length. Reduce the maximum vent length by 5' per each 90° elbow. Refer to IOM for additional piping details.									
Connections	Return/Supply Water		Gas In		Condensate Drain				
	1-1/4" NPT		1/2" NPT		1/2" PVC				
Note: Option of left, right, or rear exit for return plumbing and gas piping.									
Electrical	120 Volts AC, 60 hertz, 1 phase, Less than 12 amps (15 amp circuit recommended)								
Water Content	2.6 Gallons								
Standard Equipment	Boiler Control Module: Microprocessor based Modulating Control, Hi-Limit Control. User Display Interface: Temperature Display. Outdoor temperature sensor with cover included. Heat Exchanger: Cast Aluminum Monoblock. Combustion: Modulating Automatic Gas Valve, Modulating Burner, Direct Spark Igniter, LP Conversion Kit included. Modulating Blower, Manual Reset Casting Temperature Switch, Air Proving/Blocked Vent Safety Assembly, Air Purge Vent. Electrical: Service Switch, Service Receptacle Outlet. Other: Circulator (Taco 007 or Grundfos), Manual Reset Low Water Cutoff, Pressure Gauge, 30 PSI Safety Relief Valve, Integral Condensate Trap, Combination Painted Metal and Durable Plastic Jacket.								
Dimensions		Options Concentric Vent Kit (3"), AMB Multiple Boiler Control (For Multiple Boiler Applications - Includes outdoor reset, priority override and lead boiler run time rotation. Available in two sizes - AMB4 and AMB8 to allow stage firing of up to 8 boilers).							
Width (A)	18"	Certifications     							
Height (B)	39.375"								
Depth (C)	30.875"								
Flue Diameter (D)	3"								
Ship Wgt.	284 lbs. 128.8 kg								

All ratings and specifications subject to change.

PN 240006152 Rev. 10/12

Contractor Assistance: 800.325.5479



P.O. Box 4729
 Utica, New York 13504
 tel: 315.797.1310 • fax: 315.797.3762
 www.dunkirk.com

